

# FLOOR SAWS

## FULLY HYDRAULIC SERIES

Premium joint cutter for heavy-duty use in construction with high daily output

- Stage IV (EU) und EPA TIER 4 final (USA)
- Fully hydraulic all-wheel drive
- Blade diameter up to 1500 mm
- Fully hydraulic drive of all working functions
- Mounting of saw blade possible on right or left side
- Infinitely variable cutting shaft speed
- Standard auxiliary hydraulics for driving a suction plant
- A lot of assembly kits and accessories

Order no. 50011692

**CF-6030 97 kW**

**NEU**



### Accessories CF-6030

Pos.	Description	Order no.
--	Suction blade guard for milling/ grooving attachment	30000003
--	Normal blade guard for saw blade-Ø 1.200 mm	50009620
--	Normal blade guard for saw blade-Ø 1.500 mm	50012027
--	Suction blade guard for saw blade-Ø 600 mm	50011699
--	Suction blade guard for saw blade-Ø 1.000 mm	50011544
--	Suction blade guard for saw blade-Ø 1.200 mm	50011543
--	LED work light with magnetic holder	50001784
--	Warning beacon	30001166
1	Longitudinal attachment <b>LS-2</b>	50012065
2	Green concrete attachment	50010980
3	Milling/ grooving attachment 1.1	50012066
4	Suction plant type 6.3 hydraulic	50009742
5	Core drilling machine attachment	30000010

Technical data		CF-6030
Max. cutting depth	mm	630
Blade-Ø	mm	300 - 1500
Bevel cut		stepless to 20 degrees
Speed of cutting shaft	min <sup>-1</sup>	600 - 2800
Bore hole of blade	mm	35 + 6-hole
Blade mounting		right or left
Max. mounting width	mm	13
Max. motor output		97 / 132
Motor output (net)*	kW	97*
Motor type diesel		Doosan D34
Motor starter		electric starter
Cutting depth adjustment		electro-hydraulic
Feed		hydraulisch
Dimensions L/W/H (transport)	mm	3515 / 1320 / 1840
Weight	kg	ca. 2100

\* according to operating instructions motor