

# FLOOR SAWS

## MEDIUM SERIES

**Medium-size joint cutters suitable for cutting in narrow building sites or areas difficult to access up to heavy-duty use on building sites with high daily output**

Technical data		CF-2116 D
Max. cutting depth	mm	300
Blade-Ø	mm	600 - 800
Bore hole of blade	mm	25,4
Blade mounting		right or left
Max. mounting width	mm	20
Max. motor output	kW / PS	15,5 / 21
Motor output (net)	kW	14,7*
Motor type diesel		Hatz 2G40
Motor starter		electric starter
Cutting depth adjustment		electro-hydraulic
Feed		hydrostatic
Contents water tank	l	35
Dimensions L/W/H (transport)	mm	1300 / 1000 / 1150
Weight	kg	340

\* according to operating instructions motor

- Hydrostatic travel drive
- Large water tank
- Adjustable cutting depth indicator
- Hinged blade guard
- Electro-hydraulic lifting of saw blade
- Mounting of saw blade possible on the right or left side

Order no. 30000051

**CF-2116 D**



### Accessories CF-2116 D - green concrete conversion kit

Description	Order no.	Price €
Green concrete conversion kit for CF-2116 D, max. cutting depth 100 mm, blade-Ø 400 mm	30000053	2.319,00

Technical data		CF-1010 T
Max. cutting depth	mm	110
Blade-Ø	mm	350
Bore hole of blade	mm	25,4
Blade mounting		right
Max. mounting width	mm	20
Max. motor output	kW / PS	15,5 / 21
Motor output (net)	kW	15,5*
Motor type petrol		Honda GX-630
Motor starter		electric starter
Cutting depth adjustment		electro-hydraulic
Feed		hydraulic
Dimensions L/W/H (transport)	mm	1510/750/1650
Weight	kg	510

\* according to operating instructions motor

- Integrated cutting depth measurement
- Cutting depth indication in the digital display
- Uniform feed through hydrostatic drive
- Integrated suction unit with 2 cyclone separators
- No cutting slurries - Fast construction completion
- Height-adjustable handles

Order no. 50011688

**CF-1010 T**

**DRY CUTTING**  
with dust extraction

**NEW**

