

DRY CUTTING

Floor saws for use in dry cutting - with and without integrated dust extraction

CF-13.2 E-TR

Order no. 50004607



Note: An industrial Hoover with a suction capacity of 240 m³/h and a filter area of at least 1.5 m² is required to operate the CF-13.2 E-TR.

Technical data		CF-13.2 E-TR
Max. cutting depth	mm	95 - 120
Blade-Ø	mm	300 - 350
Bore hole of blade	mm	25,4
Blade mounting		right
Max. mounting width	mm	15
Motor output	kW	7,5
Voltage	V / Hz	400 V / 50 Hz
Amperage	A	16
Cutting depth adjustment		hand wheel
Feed		manual
Dimensions L/W/H (transport)	mm	820 / 520 / 1050 (870)
Weight	kg	106

- star-delta reversing switch
- stepless cutting depth adjustment by means of hand crank
- adjustable cutting depth indicator and parking brake
- height-adjustable and low-vibration mounted push handle
- pull-out transport handle for manual repositioning
- crane eye for easy loading of the machine

CF-1010 T

Order no. 50011688

DRY CUTTING
with dust extraction



Technical data		CF-1010 T
Max. cutting depth	mm	110
Blade-Ø	mm	350
Bore hole of blade	mm	25,4
Blade mounting		right
Max. mounting width	mm	20
Max. motor output	kW / PS	15,5 / 21
Motor output (net)	kW	15,5*
Motor type petrol		Honda GX-630
Motor starter		electric starter
Cutting depth adjustment		electro-hydraulic
Feed		hydraulic
Dimensions L/W/H (transport)	mm	1510/750/1650
Weight	kg	510

* according to operating instructions motor

- integrated cutting depth measurement
- cutting depth indication in the digital display
- uniform feed through hydrostatic drive
- integrated suction unit with 2 cyclone separators
- no cutting slurries - fast construction completion
- height-adjustable handles
- hydraulic parking brake