

FLOOR SAW CF-13.2 E-TR

Order-no.: 50004607



Electrically driven floor saws are suitable for indoor cutting where it is not permitted to use machines with combustion motors due to regulations regarding emission and/or noise protection.

Small, robust, easy to transport and equipped with a powerful electric motor - these are the attributes of the CF-13.2 E. The flexible floor saw is particularly useful for light renovations in cramped or angled interiors. The cutting depth is adjusted by handwheel, the feed is done by the operator. The operator handle is rubber-mounted and therefore particularly low in vibration. Due to its compact dimensions and easy handling, the machine is also ideal for rental.

Technical data		CF-13.2 E-TR
Max. cutting depth	mm	95 - 120
Blade-Ø	mm	300 - 350
Bore hole of blade	mm	25,4
Blade mounting		right or left
Max. mounting width	mm	15
Motor output	kW	7,5
Voltage	V / Hz	400 V / 50 Hz
Amperage	A	16
Cutting depth adjustment		hand wheel
Feed		manual
Dimensions L/W/H (transport)	mm	820 / 520 / 870
Weight	kg	106

Specially for dry cutting modified version of the CF-13.2 E

- works in counter-rotation, cutting material is ejected from the front of the cut and extracted via the extractor blade guard
- Hoover with minimum air volume of 250 m³/h and 1.5 m² filter surface required (not included in delivery)

Additional features

- Star-delta reversing switch
- Stepless cutting depth adjustment by means of hand crank
- Adjustable cutting depth indicator and parking brake
- Height-adjustable and low-vibration mounted push handle
- Pull-out transport handle for manual repositioning
- Crane eye for easy loading of the machine

Subject to technical and optical changes and further developments.