

FLOOR SAWS



ELECTRIC SERIES

For cutting tasks in enclosed spaces in which machines with internal combustion engines may not be used due to exhaust and/or noise protection regulations.

Technical data		CF-2015 E
Max. cutting depth	mm	200 - 350
Blade-Ø	mm	600 - 900
Bore hole of blade	mm	25,4
Blade mounting		right or left
Max. mounting width	mm	20
Motor output	kW	15
Voltage	V / Hz	400 V / 50
Amperage	A	32
Cutting depth adjustment		electro-hydraulic
Feed		hydrostatic
Dimensions L/W/H (transport)	mm	1700 / 750 / 1050
Weight	kg	342

- hinged blade guard for cuts directly to the wall and edges
- economic supply of cooling water via blade flanges
- saw blade mounting right or left

Technical data		1000	1200
Max. cutting depth	mm	405	505
Blade-Ø	mm	1000	1200
Bore hole of blade	mm	60	60
Blade mounting		right or left	right or left
Max. mounting width	mm	10	10
Motor output	kW	15	15
Voltage	V / Hz	400 V / 50	400 V / 50
Amperage	A	32	32
Cutting depth adjustment		electro-hydraulic	electro-hydraulic
Feed		hydrostatic	hydrostatic
Dimensions L/W/H (transport)	mm	1400 / 800 / 1200	1400 / 800 / 1300
Weight	kg	360	370

- hinged blade guard for cuts directly to the wall and edges
- supply of cooling water via blade guard
- **Inexpensive version with manual handwheel feed available on request.**

Technical data		CF-50.2 E
Max. cutting depth	mm	300 - 500
Blade-Ø	mm	800 - 1200
Bore hole of blade	mm	35
Blade mounting		right or left
Max. mounting width	mm	5
Motor output	kW	15 / 22 switchable
Voltage	V / Hz	400 V / 50
Amperage	A	32 / 63 switchable
Cutting depth adjustment		electro-hydraulic
Feed		hydrostatic
Dimensions L/W/H (transport)	mm	1550 / 940 / 1200
Weight	kg	580

- hinged blade guard for cuts directly to the wall and edges
- supply of cooling water via blade guard
- amperage switchable between 32 and 63 A

Order no. 50014432

CF-2015 E



Order no. 50015080

CF-2025 E 10

Order no. 50015081

CF-2025 E 12



Order no. 30000067

CF-50.2 E



Scope of delivery:
2 blade guards (Ø 800 and 1200 mm)