

FLOOR SAWS



MEDIUM SERIES

Medium-size floor saws suitable for cutting in narrow building sites or areas difficult to access up to heavy-duty use on building sites with high daily output

| Technical data | CF-2116 D | |
|------------------------------|-------------------|--------------------|
| Max. cutting depth | mm | 300 |
| Blade-Ø | mm | 600 - 800 |
| Bore hole of blade | mm | 25,4 |
| Blade mounting | right or left | |
| Max. mounting width | mm | 20 |
| Max. motor output | kW / PS | 15,5 / 21 |
| Motor output (net)* | kW | 14,7* |
| Motor type diesel | Hatz 2G40 | |
| Motor starter | electric starter | |
| Cutting depth adjustment | electro-hydraulic | |
| Feed | hydrostatic | |
| Contents water tank | l | 35 |
| Dimensions L/W/H (transport) | mm | 1300 / 1000 / 1150 |
| Weight | kg | 340 |

* according to operating instructions motor

- hydrostatic travel drive
- large water tank and electric water pump
- adjustable cutting depth indicator
- hinged blade guard
- electro-hydraulic lifting of saw blade
- mounting of saw blade possible on the right or left side

Order no. 30000051

CF-2116 D



Accessories CF-2116 D - green concrete conversion kit

| Description | Order no. |
|--|-----------|
| Green concrete conversion kit for CF-2116 D, max. cutting depth 100 mm, blade-Ø 400 mm | 30000053 |

