

PRODUCT INFORMATION

FLOOR SAW CF-2116 D



Order-no.: 30000051

The CF-2116 D floor saw impresses with its user-friendly overall concept and compact design. The powerful diesel engine with electric start enables optimum cutting performance of the machine. Equipped with a hydrostatic drive, this enables the floor cutter to advance evenly during cutting operation. The cutting depth is adjusted electro-hydraulically. The handles are individually height-adjustable. The large water tank (35 l) and the economical water supply to the blade through the cutting shaft ensure long and uninterrupted working.



Features

- height-adjustable handles
- large water container
- hydrostatic travel drive
- adjustable cutting depth indicator
- electro-hydraulic lifting of saw blade
- crane eye for transporting
- mounting of saw blade possible on the right or left side



Technical data	CF-2116 D	
Max. cutting depth	mm	300
Blade-Ø	mm	600 - 800
Bore hole of blade	mm	25,4
Blade mounting	right or left	
Max. mounting width	mm	20
Max. motor output	kW / PS	15,5 / 21
Motor output (net)	kW	14,7*
Motor type diesel	Hatz 2G40	
Motor starter	electric starter	
Cutting depth adjustment	electro-hydraulic	
Feed	hydrostatic	
Contents water tank	l	35
Dimensions L/W/H (transport)	mm	1300 / 1000 / 1150
Weight	kg	340

* according to operating instructions motor

Green concrete conversion kit for CF-2116 D

- cutting depth with green concrete conversion kit 100 mm
- blade-Ø with green concrete conversion kit 400 mm

Subject to technical and optical changes and further developments.

CEDIMA Diamantwerkzeug- und Maschinenbaugesellschaft mbH

Siedemeierkamp 5 • 29227 Celle / Germany • Tel. +49 5141 8854 100 • Fax +49 5141 8854 111 • e-mail: info@cedima.com • www.cedima.com