

FULLY HYDRAULIC SERIES

Premium floor saw for heavy-duty use in construction with high daily output

Order no. 50014225

CF-6032 100 kW



NEW

- stage IV (EU) und EPA TIER 4 final (USA)
- delivery incl. standard blade guard 1200 mm
- fully hydraulic all-wheel drive
- blade diameter up to 1500 mm
- fully hydraulic drive of all working functions
- mounting of saw blade possible on right or left side
- infinitely variable cutting shaft speed
- standard auxiliary hydraulics for driving a suction plant
- a lot of assembly kits and accessories

Technical data		CF-6032
Max. cutting depth	mm	630
Blade-Ø	mm	300 - 1500
Bevel cut		stufenlos bis 10°
Speed of cutting shaft	min ⁻¹	600 - 2800
Bore hole of blade	mm	35 + 6-Loch
Blade mounting		rechts oder links
Max. mounting width	mm	13
Max. motor output		100,4 / 136,5
Motor output (net)*	kW	100,4*
Motor type diesel		HD Doosan D34 (Diesel)
Motor starter		electric starter
Cutting depth adjustment		electro-hydraulic
Feed		hydraulic
Dimensions L/W/H (transport)	mm	3515 / 1320 / 1840
Weight	kg	ca. 2100

* according to operating instructions motor

Accessories CF-6032

Pos.	Beschreibung	Bestell-Nr.
--	Normal blade guard for saw blade-Ø 1.200 mm	50009620
--	Normal blade guard for saw blade-Ø 1.500 mm	50012027
--	Suction blade guard for saw blade-Ø 1.000 mm	50011544
--	Suction blade guard for saw blade-Ø 1.200 mm	50011543
--	Set of lamps, 2 worklights with support tube	30000021
--	LED worklight with magnetic holder	50001784
--	Rotating beacon 12 V with standpipe	30001166
--	LED-Rotating beacon 12 V with standpipe	50010748
1	Longitudinal attachment LS-2	50012065
3	Milling/grooving attachment 1.1 width 800 mm	50012066
--	Suction blade guard for milling/grooving attachment 800 mm	50013598
4	Suction plant type 6.3 hydraulic	50009742