

FLOOR SAW CF-6032



- Powerful low-emission Stage V (EU) common-rail -diesel with automatic cold-start system
- All-wheel drive via hydraulically driven wheel hub motors
- Fully hydraulic drive of all working functions
- mounting of saw blade possible on right or left side
- Infinitely variable cutting shaft speed up to 20°
- Infinitely variable cutting shaft speed
- Standard auxiliary hydraulics for driving a suction plant
- Water supply through the cutting shaft
- Maximum ease of operation
- Supplied with 1200 mm blade guard as standard!

Premium joint cutter for heavy-duty use in construction with high daily output

The CF-6032 is the largest and also the most powerful CEDIMA floor cutter. The water-cooled 4-cylinder common rail diesel engine complies with the latest exhaust emission standard and thus meets all environmental protection requirements. All hydraulic work functions are controlled electronically via a control panel on the driver's seat and displayed on a clear 7" colour display. The ergonomic seat and steering wheel are adjustable, ensuring that the operator is always in the best position to observe the cutting line. A wide range of expansion options make the CF-6032 a universal powerhouse for processing traffic areas made of concrete or asphalt.

Technical data		CF-6030
Max. cutting depth	mm	630
Blade-Ø	mm	300 - 1500
Bevel cut		stepless to 20 degrees
Speed of cutting shaft	min ⁻¹	600 - 2800
Bore hole of blade	mm	35 + 6-hole
Blade mounting		right or left
Max. mounting width	mm	13
Max. motor output		97 / 132
Motor output (net)*	kW	97*
Motor type diesel		Doosan D34
Motor starter		electric starter
Cutting depth adjustment		electro-hydraulic
Feed		hydraulisch
Dimensions L/W/H (transport)	mm	3515 / 1320 / 1840
Weight	kg	ca. 2100

* according to operating instructions motor

Subject to technical and optical changes and further developments.