

DIAMOND DRILL BITS



PROFESSIONAL USE - DRY DRILLING

Diamond drill bit			Re-tipping
Ø -mm-	No. of segments	Order no.	Order no.
41	3	50006630	50006743
51	3	50006631	50006744
61	4	50006632	50006745
71	4	50006633	50006746
81	4	50006634	50006747
91	4	50006635	50006748
101	5	50006636	50006749
111	5	50006637	50006750
121	5	50006638	50006751
126	5	50006639	50006752
131	5	50006640	50006753
141	5	50006641	50006754
151	6	50006642	50006755
161	6	50006643	50006756
181	6	50006644	50006757
201	6	50006645	50006758
225	7	50006646	50006759

- application in masonry, lime sand-stone, Poroton, bricks with dry drilling systems and hand-held drill motor
- usable length 300 mm
- connection 1 1/4" UNC-bushing



BB-1 T MAXX



- application: Lime sand brick (highly compacted), Concrete and reinforced concrete (limited) with dry drilling systems and hand drill motors
- usable length 300 mm - connection 1 1/4" UNC-bushing
- Also for drill motors with soft impact suitable.

The matching drill motors with soft impact can be found on page 62 of this price list.

Diamond drill bit		
Ø -mm-	No. of segments	Order no.
32	4	50011256
42	4	50011257
52	5	50011258
62	5	50011259
72	5	50011260
82	6	50011261
92	6	50013307
102	7	50011262
112	7	50011263
122	8	50011264
127	8	50013308

Diamond drill bit		
Ø -mm-	No. of segments	Order no.
132	8	50011265
142	8	50011266
152	8	50011267
162	9	50011268
172	9	50014262
182	9	50011269
192	10	50014263
202	10	50011270
212	10	50014374
226	11	50014264
250	11	50014375

Segments with precisely positioned diamonds



BK SYNCRO MAXX DRY

