DIAMOND RING DRILL BITS

PROFESSIONAL USE - CONCRETE / NATURAL STONE

BCDK MAXX

- ring drill bit for reinforced concrete with medium-hard aggregates and low to medium shares of reinforcement
- usable length 300 mm, connection R½" bushing
- segment ring (W x H): 2,5 x 10,0 mm

Diamond drill bit		Re-tipping	Diamond segment ring	
Ø -mm-	Order no.	Order no.	Order no.	Segment ring W x H -mm-
12	50008652	50008666	50007635	2,5 x 10
14	50008653	50008667	50007636	2,5 x 10
16	50008654	50008668	50007637	2,5 x 10
18	50008655	50008669	50007638	2,5 x 10
20	50008656	50008670	50007639	2,5 x 10
22	50008657	50008671	50007640	2,5 x 10
24	50008658	50008672	50007641	2,5 x 10
25	50008659	50008673	50007642	2,5 x 10
28	50008660	50008674	50007643	2,5 x 10
30	50008661	50008675	50007644	2,5 x 10
32	50008662	50008676	50007645	2,5 x 10
35	50008663	50008677	50007646	2,5 x 10
38	50008664	50008678	50007647	2,5 x 10
41	50008665	50008679	50007648	2,5 x 10

GCDK SOLID

- use in granite and natural stone
- usable length 300 mm, connection R½" bushing
- segment ring (W x H): 2,5 x 10,0 mm

Diamond drill bit		Re-tipping	Diamond segment ring	
Ø -mm-	Order no.	Order no.	Order no.	Segment ring W x H -mm-
12	50008680	50008694	50007649	2,5 x 10
14	50008681	50008695	50007650	2,5 x 10
16	50008682	50008696	50007651	2,5 x 10
18	50008683	50008698	50007652	2,5 x 10
20	50008684	50008699	50007653	2,5 x 10
22	50008685	50008700	50007654	2,5 x 10
24	50008686	50008701	50007655	2,5 x 10
25	50008687	50008702	50007657	2,5 x 10
28	50008688	50008703	50007658	2,5 x 10
30	50008689	50008704	50007659	2,5 x 10
32	50008690	50008705	50007663	2,5 x 10
35	50008691	50008706	50007664	2,5 x 10
38	50008692	50008707	50007665	2,5 x 10
41	50008693	50008708	50007667	2,5 x 10