

DRILL MOTORS

Drill-Ø up to 160 mm



Only dry drilling possible!

NEW



NEW

Delivery of our drilling motors drill-Ø up to 160 mm incl. transport case!

Technical data		DKS-15 SP	C-BMH-160	C-BM-17
Order no.		50014501	30001108	50014459
Drill-Ø from-to (in abrasive materials)		30-150 (30-180)	16-160 --	20 - 160 (20 - 180)
Dry drilling/soft impact		Yes / Yes	No / No	Yes / No
Speed of rotation		700 / 1700	600 / 980 / 2780	540 / 1200 / 2520
Motor output		1,34	2,0	2,0
Voltage		230 / 50	230 / 50~60	230 / 50
Connecting thread		1 1/4" UNC	R 1/2" + 1 1/4" UNC	1 1/4" UNC + R 1/2"
Dimensions L/W/H		510 / 100 / 280	437 / 115 / 289	420 / 100 / 300
Weight		5,8	6,4	6,9
Recommended drill rigs / columns		H-150, P-250	H-150, P-250	H-150, P-250

Drill-Ø up to 350 mm



NEW



NEW

Technical data		C-BMS-350	C-BM-32	C-BM-32 S
Order no.		30001109	50014460	50014461
Drill-Ø from-to (in abrasive materials)		45 - 350 --	50-350 400	50 - 300 --
Dry drilling/soft impact		No / No	No / No	Yes / Yes
Speed of rotation		270 / 480 / 780	230 / 460 / 720	230 / 460 / 720
Motor output		3,5	3,2	3,2
Voltage		230 / 50~60	230 / 50	230 / 50
Connecting thread		1 1/4" UNC	1 1/4" UNC	1 1/4" UNC
Dimensions L/W/H		545 x 150 x 210	550 / 140 / 170	610 / 140 / 170
Weight		11,8	12,8	13,5
Recommended drill rigs / columns		P-250, P-3000, P-500, P-6000	P-250, P-3000, P-500, P-6000	P-250, P-3000, P-500, P-6000