

AUTOMATIC WIRE SAWS

CSA-100 H

Order no. 30000463



Technical data		CSA-100 H
Storage rolls	pcs.	8
Wire in storage min./max.	m	4,0 / 10,5
Max. wire storage capacity	m	6,5 + 1,5*
Motor	hydraulic motor	
Weight without motor	kg	54,0
Weight with motor	kg	60,8
Oil flow feed	l/min	1 - 15
Max. operating pressure feed	bar	100
Dimensions L/W/H	mm	1050 / 300 / 460

* by moving the machine on the guide tube

Technical data		Hydraulic drive
Max. output hydraulic motors	kW	20
Oil quantity hydraulic drive	l/min	25 - 55
Max. working pressure drive	bar	250



Hydraulic power pack HAG-12.12
with hydraulic control panel HSP-12

Application set wire saw CSA-100 H

Order no.	Type	Description
30000463	CSA-100	automatic wire saw with 2 mini swivel rolls and ground mounting foot, without drive motor
30000467	-	wire guard set with water collecting function
30000425	HM-19	hydraulic drive motor 19 cm ³
50008712	HAG-12.22	hydraulic power pack with hydraulic control panel
30000423	-	set of hoses 3-parts, 10 m long, for drive of drive wheel (wire saw)
30001011	-	set of hoses 2-parts, 10 m long, (for feed at wire sawing with HAG-12.22)

Additional suitable components

Order no.	Type	Description
30000426	HM-23	hydraulic drive motor 23 cm ³ , alternatively to HM-19
50008713	HAG-12.12	hydraulic power pack
30000429	HSP-12	hydraulic control panel
30000421	-	set of hoses 2-parts, 10 m long (for feed at wire sawing with HSP-12)
30001033	MF-6000	foot for mounting to wall or ground with mounting tube
30001135	-	wheel kit for mounting foot
30000465	-	precision swivel foot 360° with mounting tube
30000667	-	DS-350, anchoring dowel set for drill-Ø up to 350 mm (incl. 25 dowels)

