SPECIAL MACHINES



HAG-12.22

HYDRAULIC POWER PACKS

Order no. 50008713

HAG-12.12



Order no. 50008712

HAG-12.22

Technical data		HAG-12.12
Electric motor, air-cooled	kW	15
Voltage/amperage/ frequency	V / A / Hz	400 / 32 / 50
Motor speed	min ⁻¹	3000
Number of hydraulic pumps		2 parallel conveying gear pumps
Oil flow capacity, operating pressure	:	
oil circuit/ 1. main circuit		30I/min at 250 bar
oil circuit / 2. main circuit		45 l/min at 160 bar
Oil flow rate control circuit	I/min	15
Oil quantity in tank	- 1	11,0
Dimensions L/W/H	mm	850 / 600 / 1200
Total weight	kg	ca. 188 (incl. hydraulic oil)

- automatic soft start
- double active motor monitoring (temperature / current)
- double gear pump
- 2 switchable oil flow rates
- solenoid valve and electronics for remote shut-off via emergency stop
- removable electric motor for easy transport

	HAG-12.22
kW	15
V / A / Hz	400 / 32 / 50
min ⁻¹	3000
Number of hydraulic pumps	
	30I/min at 250 bar
	15 l/min at 250 bar
	45 I/min at 160 bar
	6 l/min, infinitely at 0-60 bar
1	11,0
mm	850 / 600 / 1200
kg	ca. 190 (incl. hydraulic oil)
	V/A/Hz min ⁻¹

- automatic soft start
- double active motor monitoring (temperature / current)
- triple gear pump simultaneous supply of three oil circuits
- dditional control circuit and hydraulic control panel for feed control of wire saws or wall saws

• removable electric motor for easy transport

Accessories for hydraulic power packs

Order no.	Туре	Description
30000533	ABV-10	assembly valve for pressure reduction for 170 bar for hydraulic hand-held saw and chain saw
30000429	HSP-12	hydraulic control panel

