

Order Nr. 50008713

**HAG-12.12**

Order Nr. 50008712

**HAG-12.22**



**NEW**

Operating hours counter  
in the control box

Robust, user-friendly hydraulic power  
packs specially designed to drive electro-  
hydraulic wall and wire saws.



| Technical data                     |                   | HAG-12.12                         |
|------------------------------------|-------------------|-----------------------------------|
| E-motor, air-cooled                | kW                | 15                                |
| Voltage/current/frequency          | V / A / Hz        | 400 V/32 A/50 Hz                  |
| Speed                              | min <sup>-1</sup> | 3,000 min                         |
| Number of hydraulic pumps          |                   | 2 parallel gear pumps             |
| Oil flow rate, nominal pressure:   |                   |                                   |
| Working circuit / 1st main circuit |                   | 30 l/min at 250 bar               |
| Working circuit / 2nd main circuit |                   | 45 l/min at 160 bar               |
| Oil delivery rate control circuit  | l/min             | 15                                |
| Oil tank capacity                  | l                 | 11,0                              |
| Dimensions L / W / H               | mm                | 850 / 600 / 1200                  |
| Total weight                       | kg                | approx. 188 (incl. hydraulic oil) |

- Automatic soft start
- Double active motor monitoring (temperature /current)
- Dual gear pump
- 2 switchable oil flow rates
- Solenoid valve and electronics for remote emergency shut-off
- Removable electric motor for easy transport

## Equipment hydraulic power packs

| Order Nr. | Type   | Description                                                                               |
|-----------|--------|-------------------------------------------------------------------------------------------|
| 30000533  | ABV-10 | Attachment valve for pressure reduction to 170 bar for hydraulic hand-held and chain saws |
| 30000429  | HSP-12 | Hydraulic control panel                                                                   |

Subject to technical and optical changes and further developments.

| Technical data                     |                   | HAG-12.22                                |
|------------------------------------|-------------------|------------------------------------------|
| E-motor, air-cooled                | kW                | 15                                       |
| Voltage/current/frequency          | V / A / Hz        | 400 V/32 A/50 Hz                         |
| Speed                              | min <sup>-1</sup> | 2.902                                    |
| Number of hydraulic pumps          |                   | 3 parallel gear pumps                    |
| Oil flow rate, nominal pressure:   |                   |                                          |
| Working circuit / 1st main circuit |                   | 30 l/min at 250 bar                      |
| Working circuit / 2nd main circuit |                   | 15 l/min at 250 bar                      |
| 1st + 2nd main circuit             |                   | 45 l/min at 160 bar                      |
| Oil delivery rate control circuit  |                   | 6 l/min, infinitely variable at 0-60 bar |
| Oil tank capacity                  | l                 | 11,0                                     |
| Dimensions L / W / H               | mm                | 850 x 600 x 1200                         |
| Total weight                       | kg                | approx. 190 (incl. hydraulic oil)        |

- Automatic soft start
- Double active motor monitoring (temperature /current)
- Triple gear pump - simultaneous supply of three oil circuits
- Additional control circuit and hydraulic control panel for feed control of wire or wall saws
- Removable electric motor for easy transport

