

MINI CRANE CMK-400 (DK)

The Böcker mini crane is the ideal tool for moving large-format construction elements. Both mini crane models guarantee safe and error-free work as well as a significant acceleration of the work process.



- Hook height 4.5 m, telescopic to 6.0 m
- Completely hot-dip galvanised (frame, tower, jib)
- Chassis with electric motor drive
- Wheel breakage protection and foot protection as standard
- Screw jack for raising and lowering mast and jib by electric motor (electric cylinder)
- Hoist with quick and fine lift, 8 m chain and load hooks
- Water-repellent protective hood
- Only one electrical connection required for all functions
- Optional two-speed rotary and cross-travel drives, rotary drive can be easily disengaged
- One-tong system guarantees effective work
- Smooth-running rotating mechanism ensures easy working
- Low-backlash locking of the tower
- Concrete ballast weight 960 kg with practical transport lug
- By tilting the jib, up to 5 mini cranes can be loaded on one truck
- Offset option for forklift and crane transport
- Optionally with cable or radio remote control (easy to retrofit!)

Technical data		CMK-400 DK	CMK-400
Electric travel drive		Ja	Ja
Electric tower drive		Ja	Nein
Electric trolley drive		Ja	Nein
Load capacity at 5.0 m outreach	kg	400	400
Load capacity at 4.0 m outreach	kg	500	500
Hook height at 5.2 m tower height	m	4,5	4,5
Hook height at 6.7 m tower height	m	6,0	6,0
Wall height at 5.2 m tower height	m	3,75	3,75
Wall height at 6.7 m tower height	m	5,25	5,25
Lifting speed	m/min	9 / 1,5*	9 / 1,5*
Weight with ballast		2160	2050
Ballast weight		960	960
Chassis dimensions L / B	m	250 / 190	250 / 190
Transport length	m	6,9	6,9
Transport height	m	2,1	2,1

*) Fine lift



Subject to technical and optical changes and further developments.