

CONCRETE SLURRY SEPARATOR

CBS-1500

Order no. 30000198

Application

- the mobile concrete slurry separator CBS-1500 is able to store large slurry quantities
- the solids are filtered and the water is recycled to the working process


Features

- independent of supply lines due to current generator of its own
- large-sized filter systems for long working periods without interruptions
- clear water tanks with a net capacity of 1100 litres
- removable solids container with fork-lift plates for comfortable discharge of the filter cake
- collecting basin with strainer for storage of slurry
- sonic signal and automatic shutdown when filter is completely filled
- discharge of filter contents in only 30 seconds without interruption of cutting operation
- assembly of the plant on high-grade tandem axle trailer with approval for road service

Required drawing vehicle

towing device	bolt-type
braked trailer load	3500 kg
vertical load	150 kg

Technical data		CBS-1500
max. filtration performance	l/h	1500
capacity of filter system		96 l - solids
contents of clear water tanks -net-	l	2 x 550
capacity of slurry collecting basin	l	550
capacity of solids container		approx. 3 filter fillings
dimensions L/W/H	mm	5270 / 2165 / 2580
unloaded weight	kg	2240
weight - with filled clear water tanks -	kg	3340



Left: collecting basin with strainer; centre above: filter element; centre below: solids container



From left to right: current generator, clear water tanks, slurry pump



The filter is emptied by tearing apart the filter elements.



The solids are collected in a container.