

LARGE SIZED STONE BLOCKS



Technical data		CTS-265.2	
Cutting depth	mm	140	265
Cutting length	mm	700	700
Blade-Ø	mm	500	650
Bore hole of blade	mm	25,4	
Drive motor	kW/ V/ Hz	5,5 / 400 / 50	
Content water container/ bucket	liter	50	
Dimension L / W / H	mm	1750 / 830 / 1780	
Transport L / W / H		1750 / 900 / 1530	
Weight	kg	240	

- **Now with longer cutting length!**
- operating hours meter
- pendulum cutting head
- removable stainless steel water tray
- roller table with feed rod
- lockable castor wheels and extra large wheels for easy transport
- crane eyes for easy relocation on the construction site
- cooling water supply via electric water pump

Order no. 50007779

CTS-265.2



Accessories and spare parts for table saws

Pos.	Order no.	Description	For operation with
1	30000228	Jolly table for mitre cuts, pivoting by 45° on both sides, with angle scale	CTS-56, CTS-175.1, CTS-200
2	30000201	Angle stop with scale	CTS-56, CTS-57 G, CTS-26 Series, CTS-81, CTS-175.1, CTS-200
3	30000225	Prism for cutting round objects, with rubber mat against torsion	CTS-56, CTS-57 G, CTS-175.1, CTS-200
4	30000202	Auxiliary table with rubber mat for cutting long objects, 614 x 586 mm, with lay-on edge and slide-in feet	CTS-26 Series, CTS-81 L
5	70008154	Spare part electric immersion pump CEP-700 (without connecting plug) Technical details: 230 V; 50 Hz; 0,4 AMP; 50 W; Protective system: ISO-F IP X8; feed rate: 11,6 l/min lifting height: 1,5 m; Length of supply: 4 m • dimensions: 71 x 95 x 108 mm	CTS-56, CTS-57 G, CTS-26 Series, CTS-81 Serie, CTS-175.1, CTS-200
6	70008155	Spare part electric immersion pump CEP-1600 (without connecting plug) Technical details: 230 V; 50 Hz; 0,7 AMP; 60 W; Protective system: ISO-F IP X8; feed rate: 25 l/min lifting height: 2,5 m; Length of supply: 4 m • dimensions: 71 x 95 x 123 mm	CTS-265.2, CTS-375.3
7	70012343	Spare part connecting plug IP 68 or electric immersion pump, Simplifies the replacement of the water pump	All Cedima-Table saws

